


TURF AND IVY
 SOLUTIONS
It makes sense.



TOPAZ

USES


- ▶ Landscape
- ▶ Lawns
- ▶ Playgrounds
- ▶ Traffic Medians
- ▶ Pet Areas
- ▶ Commercial or Residential
- ▶ Light-Heavy Traffic

HOLLOW BLADE

SPECIFICATIONS

Pile Height:	1-3/4"
Turf Gauge:	3/8"
Face Weight:	60 oz./yd ²
Backing Weight:	26 oz./yd ²
Total Weight:	86 oz./yd ²
Stitch Rate:	14/10cm
Stitches/M ² :	14700
Material/Dtex:	PE 9300 + PP 4000
Color:	Olive Green and Emerald Green with Brown and Green Thatching
Type Of Fiber:	PE Monofilament and PP Curled
Infill Amount:	1.0 lb./psf.
Primary Backing:	Premium T&I Backing
Tuft Bind:	11+ lb./force (ASTM D1335)
Blade Type:	Hollow Shape
Permeability:	63.7 inches/hr. (ASTM F1551)
Melting Point:	176 °F (ASTM D2859)
Grab Tear MD:	>200 lb./force (ASTM D5034)
Grab Tear CMD:	≥200 lb./force (ASTM D5034)
Roll Width:	15 ft
Roll Length:	100 ft
Sq. Ft. Per Roll:	1500
Total Roll Weight:	893 lbs

 15 Year Manufacturer's Warranty
8 Year Manufacturer's High Traffic Warranty

 Flo-Rite Drainage Technology

