




TURF AND IVY

SOLUTIONS

It makes sense.




SOD STAPLE 6" x 1" x 6"
DRAINAGE PASS THROUGH FOR WATER IN PUNCHED HOLES THROUGHOUT BACKING

SEAMING TAPE

SPECIFICATIONS


YARN TYPE POLYETHYLENE M SHAPE BLADE
THATCH YARN TYPE POLYPROPYLENE CURLED AS THATCH
PILE HEIGHT 1 3/4"
TURF GAUGE 1/2"
FACE WEIGHT 65 OZ YD²
BACKING WEIGHT 25 OZ YD²
TOTAL WEIGHT 90 OZ YD²
STITCH RATE 24/10 CM
STITCHES/M² 18960
COLOR EMERALD GREEN AND LIME GREEN WITH BROWN AND GREEN THATCHING
ROLL SIZE (FEET) 15' x 100'
MAXIMUM DRAIN RATE >30 INCHES PER HOUR



SECTION



SEAMING
SOD STAPLES ARE RECOMMENDED TO SEAM THE SEAMS




SECURING TURF TO BASE
BRIGHT COMMON 40D/60D NAILS OR GALVANIZED NAILS 6' APART ALONG PERIMETER SEAMS.



POWER BROOM AFTER INSTALLATION IS COMPLETE

NOTES:

1. THE GRASS MUST BE INSTALLED AND SEAMED WITH ADJACENT PIECES RUNNING IN THE SAME DIRECTION. SEAMS SHOULD BE GLUED WITH SUITABLE SEAMING GLUE AND SEAMING CLOTH, OR RECOMMENDED SEAMING TECHNIQUES.
2. COLOR: EMERALD GREEN AND LIME GREEN WITH BROWN AND GREEN THATCHING.
3. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
4. DO NOT SCALE DRAWING.
5. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
6. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.



PERFORMANCE SERIES | ENGINEERED BLADES

ROYAL PEARL

5006-013



5 Centerpointe Drive - Suite 400
Lake Oswego, OR 97035



Office Number:
1.888.453.5979

turfandivy.com