



**turf&ivy**  
solutions

## HARRISON IVY

COLOR/FINISH:DARK GREEN



### LEAF SPECS

Width	1-1/2"--2-1/2"
Length	2"- 3-1/5"
Type	Assorted



EASY CUT TO FIT

### MATERIAL SPECIFICATIONS

Low density polyethylene (LDPE)

Density	.957
Minimum Temp.	-76° F
Maximum Temp.	250° F
Shade Percentage	85%
Backing Thickness	1/8"




ECO-FRIENDLY

### PANEL SIZE/WEIGHT

Height (Inches)	2"
Length (Inches)	23-3/5"
Width (Inches)	23-3/5"
Weight (Lbs)	2.9 lbs/panel

### BACKING GRID



### Ivy Installation Instructions

- Determine how much surface area needed to be covered.
- Order 3-5% extra ivy as you will have scrap during the installation process.
- The ivy comes in 23-3/5" x 23-3/5" squares.
- Ivy is dye lot sensitive, if you reorder ivy for an existing area make sure to ask for the same dye lot as the original order.
- Use scissors or a carpet knife to trim the ivy to fit the surface area as needed.

### Ivy Benefits and Features

- ★ Connect and cut for a perfect fit
- ★ 3 year manufacturer's warranty
- ★ Low maintenance
- ★ Graffiti deterrent
- ★ UV stable
- ★ Cleans easy



5 Centerpointe Drive - Suite 400  
Lake Oswego, OR 97035



Office Number:  
1.888.453.5979

[turfandivy.com](http://turfandivy.com)



## HARRISON IVY

### MANUFACTURING MATERIAL SAFETY DATA SHEET

#### A. Identity

Product Model: Harrison Ivy Fire resistant LDPE  
Manufacturer:

Turf and Ivy Solutions, Inc.  
5 Centerpointe Dr Ste 400  
Lake Oswego, OR 97035

Emergency telephone number: 1-888-453-5979

#### B. Hazardous Ingredients

This product is considered to be a non-hazardous chemical under the Federal Occupational Safety and Health Administration Hazard Communication Standard 29CFR1910.1200

#### C. Physical Data

Boiling Point: n/a  
Vapor Pressure: n/a  
Vapor Density: n/a  
Melting Point: 1760 F/800C (Leaves)  
Specific Gravity: (H2O=1) 0.94 leaves  
Percent volatile by volume: n/a  
Evaporation Rate: n/a/  
Appearances: Solid  
Odor: None

#### D. Fire Hazard Data

Unusual fire and explosion hazards: None  
Flashpoint: 6050F/318oC  
Extinguishing Method: Water, Foam, Carbon Dioxide  
Fire Fighting Equipment: Wear protective pressure, Self-contained, Breathing Apparatus  
This product is resistant to damage and spreading of ignition in typical exposures such as lighted cigarette dropped on the surface.



5 Centerpointe Drive - Suite 400  
Lake Oswego, OR 97035



Office Number:  
1.888.453.5979

[turfandivy.com](http://turfandivy.com)



## HARRISON IVY

### MANUFACTURING MATERIAL SAFETY DATA SHEET

#### E. Reactivity Data

Stability: (Conditions to avoid) Polymer may decompose under fire conditions to give off hazardous products

Dissolution: Softening or discoloration may occur with yarn, phenol, formic acid, other acidic exposures below pH5

Hazardous Decomposition Products: Carbon Dioxide, Carbon Monoxide, Nitrogen Oxides, Traces of Hydrogen Cyanide

#### F. Health Hazard Information

No health hazards are evident from MSDS documentation of constituents of this product, in the form presented when installed and used for its intended application as a synthetic turf product.

#### G. Environmental & Disposal Information

This product is in compliance with EPA guidelines (RCRA, CFR261, and TCLP) and is compliant with Executive Order 13101, "Greening the government through waste prevention, recycling, and federal acquisition."

Disposal Procedures: Safe for landfills; Can be processed and used as a combustible fuel where proper recycling facilities are available.

#### H. Legal Disclaimer

While the information set forth herein is believed to be accurate and complete as of the date hereof, Turf and Ivy Solutions makes no warranty with respect thereto and disclaims all liability from release thereon.

5 Centerpointe Drive - Suite 400, Lake Oswego, OR 97035

#### I. Date of Issue

April 1, 2024



5 Centerpointe Drive - Suite 400  
Lake Oswego, OR 97035



Office Number:  
1.888.453.5979

[turfandivy.com](https://turfandivy.com)



**HARRISON IVY**

PRODUCT CUT SHEET  
BLOCK/CONCRETE WALL MOUNT




**LEGEND**

1. 24"x24" PANEL.
2. ADJACENT INTERLOCKING PANEL.
3. INTERLOCKING TAB.
4. TWO (2) PER 12" SQUARE PANEL, OR PER MANUFACTURER RECOMMENDATION.

SECURE TILE IVY SQUARE FROM THE TOP OF THE PANEL THROUGH FORMED HOLES.

5. SECURE PANEL AT FOUR (4) LOCATIONS WHEN PANELS ARE AT THE TOP AND BOTTOM OF WALL.



FENDER WASHER  
3/16" X 1 - 1/4" X 1 1/4"



CONCRETE ANCHOR  
DIAMETER  
3/16" X 1/4"

## HARRISON IVY

### PRODUCT CUT SHEET CHAINLINK/ROD IRON FENCING MOUNT




#### LEGEND

1. 24" x 24" PANEL.
2. ADJACENT INTERLOCKING PANEL.
3. INTERLOCKING TAB.
4. OUTSIDE PERIMETER TWO (2) PER 12" SQUARE PANEL EVERY 6", OR MANUFACTURER RECOMMENDATION

SECURE TILE/PANEL THRU BAND OR FORMED HOLES

5. INSIDE PERIMETER SECURE TILES/PANELS EVERY SQUARE FOOT, OR MANUFACTURER RECOMMENDATION



8" – 14" CABLE TIES  
OUTDOOR USE  
UV RESISTANT  
FLEXIBLE NYLON MATERIAL